

# DIESEL STANDBY GENERATOR SETS WITH JOHN DEERE ENGINES, 60 HZ, 1800 RPM

| MODEL          | 130°C<br>R/R<br>STBY<br>KW | VOLTS | PHASE | FULL<br>LOAD<br>MAX<br>GEN<br>AMPS |
|----------------|----------------------------|-------|-------|------------------------------------|
| SPJD-300-1-1   | 30                         | 240   | 1     | 125                                |
| SPJD-300-3-2   |                            | 208   | 3     | 104                                |
| SPJD-300-3-3   |                            | 240   |       | 90                                 |
| SPJD-300-3-4   |                            | 480   |       | 45                                 |
| SPJD-300-3-16  |                            | 600   |       | 36                                 |
| SPJD-600-1-1   | 60                         | 240   | 1     | 250                                |
| SPJD-600-3-2   |                            | 208   | 3     | 208                                |
| SPJD-600-3-3   |                            | 240   |       | 181                                |
| SPJD-600-3-4   |                            | 480   |       | 90                                 |
| SPJD-600-3-16  |                            | 600   |       | 72                                 |
| SPJD-800-1-1   | 75                         | 240   | 1     | 312                                |
| SPJD-800-3-2   | 80                         | 208   | 3     | 278                                |
| SPJD-800-3-3   |                            | 240   |       | 241                                |
| SPJD-800-3-4   |                            | 480   |       | 120                                |
| SPJD-800-3-16  |                            | 600   |       | 96                                 |
| SPJD-1000-1-1  | 100                        | 240   | 1     | 416                                |
| SPJD-1000-3-2  |                            | 208   | 3     | 347                                |
| SPJD-1000-3-3  |                            | 240   |       | 301                                |
| SPJD-1000-3-4  |                            | 480   |       | 151                                |
| SPJD-1000-3-16 |                            | 600   |       | 120                                |
| SPJD-1250-1-1  | 125                        | 240   | 1     | 521                                |
| SPJD-1250-3-2  |                            | 208   | 3     | 434                                |
| SPJD-1250-3-3  |                            | 240   |       | 376                                |
| SPJD-1250-3-4  |                            | 480   |       | 188                                |
| SPJD-1250-3-16 |                            | 600   |       | 150                                |
| SPJD-1550-1-1  | 155                        | 240   | 1     | 646                                |
| SPJD-1550-3-2  | 151                        | 208   | 3     | 525                                |
| SPJD-1550-3-3  |                            | 240   |       | 455                                |
| SPJD-1550-3-4  | 155                        | 480   |       | 233                                |
| SPJD-1550-3-16 |                            | 600   |       | 186                                |
| SPJD-2100-3-2  | 210                        | 208   | 3     | 729                                |
| SPJD-2100-3-3  |                            | 240   |       | 632                                |
| SPJD-2100-3-4  |                            | 480   |       | 316                                |
| SPJD-2100-3-16 |                            | 600   |       | 600                                |

## NOTES FOR SPJD SERIES GEN-SETS:

**OPEN UNITS:** EQUIPPED WITH MANIFOLD/TURBO EXHAUST PIPE, FLEX CONNECTOR, AND CLAMPS (FOR SILENCER SEE PAGE 12).

**LEVEL 2:** SOUND ABSORBING FOAM WITH 4 LB. DENSITY THROUGHOUT HOUSING INTERIOR AND INCLUDES AIR DAMS, GENERATOR END AIR DUCT (80KW THRU 425KW ONLY), AND "CRITICAL" GRADE SILENCER.

VOLTAGE SUFFIX NUMBER CODES. SUFFIX #1-1 = 1 PHASE—120/240 VOLTS; SUFFIX #3-2 = 3 PHASE 120/208 VOLTS; SUFFIX #3-3 = 3 PHASE—120/240 VOLTS; SUFFIX #3-4 = 3 PHASE—277/480 VOLTS, SUFFIX #3-16 = 3 PHASE-600 VOLT.

**SP, SPJD, SPVD, AND SPMD STANDBY GEN-SET STANDARD ACCESSORIES INCLUDE:** 12/24VDC "FLOAT" BATTERY CHARGER, SILENCER, FLEXIBLE OIL AND RADIATOR DRAIN HOSE, PROGRAMMABLE DIGITAL CONTROLLER, BATTERY TRAY AND CABLES, AND CIRCUIT BREAKER (SILENCER NOT INCLUDED FOR OPEN UNITS).