

# LPG/NATURAL GAS STANDBY GENERATOR SETS WITH PSI ENGINES, 60 HERTZ, 1800 RPM

MODEL	130°C R/R STANDBY		VOLTS	PHASE	FULL LOAD MAX GEN AMPS
	LPG KW	NAT GAS KW			
SP-250-1-1	25	25	240	1	104
SP-250-3-2			208	3	87
SP-250-3-3			240		75
SP-250-3-4			480		38
SP-250-3-16			600		30
SP-300-1-1	30	28	240	1	125
SP-300-3-2			208	3	104
SP-300-3-3			240		90
SP-300-3-4			480		45
SP-300-3-16			600		36
SP-410-1-1	41	40	240	1	171
SP-410-3-2	40		208	3	139
SP-410-3-3			240		120
SP-410-3-4			480		60
SP-410-3-16			600		48
SP-520-1-1	50	50	240	1	208
SP-520-3-2	52	52	208	3	181
SP-520-3-3			240		157
SP-520-3-4			480		78
SP-520-3-16			600		62
SP-620-1-1	60	58	240	1	250
SP-620-3-2	62	60	208	3	215
SP-620-3-3			240		187
SP-620-3-4			480		93
SP-620-3-16			600		72
SP-8005N-1-1	NOT AVAIL. ON LPG	75	240	1	312
SP-8005N-3-2		80	208	3	278
SP-8005N-3-3			240		241
SP-8005N-3-4			480		120
SP-8005N-3-16			600		96
SP-960-1-1	80	95	240	1	396
SP-960-3-2		96	208	3	334
SP-960-3-3			240		289
SP-960-3-4			480		145
SP-960-3-16			600		115
SP-1200-1-1	110	120	240	1	500
SP-1200-3-2			208	3	416
SP-1200-3-3			240		361
SP-1200-3-4			480		180
SP-1200-3-16			600		144
SP-1500-1-1	130	150	240	1	625
SP-1500-3-2			208	3	521
SP-1500-3-3			240		451
SP-1500-3-4			480		225
SP-1500-3-16			600		180

MODEL	130°C R/R STANDBY NAT GAS KW	VOLTS	PHASE	FULL LOAD MAX GEN AMPS
SP-2000-3-2	200	208	3	694
SP-2000-3-3		240		602
SP-2000-3-4		480		301
SP-2000-3-16		600		241
SP-2650-3-2	265	208	3	921
SP-2650-3-3		240		798
SP-2650-3-4		480		399
SP-2650-3-16		600		319
SP-3000-3-2	300	208	3	1042
SP-3000-3-3		240		903
SP-3000-3-4		480		452
SP-3000-3-16		600		361
SP-3500-3-2	350	208	3	1216
SP-3500-3-3		240		1054
SP-3500-3-4		480		527
SP-3500-3-16		600		421
SP-4000-3-2	400	208	3	1390
SP-4000-3-3		240		1204
SP-4000-3-4		480		602
SP-4000-3-16		600		480
SP-4250-3-2	425	208	3	1476
SP-4250-3-3		240		1280
SP-4250-3-4		480		640
SP-4250-3-16		600		512

## NOTES FOR SP SERIES GEN-SETS:

**OPEN UNITS:** EQUIPPED WITH MANIFOLD/TURBO EXHAUST PIPE, FLEX CONNECTOR, AND CLAMPS (FOR SILENCER SEE PAGE 12).

**LEVEL 2:** SOUND ABSORBING FOAM WITH 4 LB. DENSITY THROUGHOUT HOUSING INTERIOR AND INCLUDES AIR DAMS, GENERATOR END AIR DUCT (80KW THRU 425KW ONLY), AND "CRITICAL" GRADE SILENCER.

VOLTAGE SUFFIX NUMBER CODES. SUFFIX #1-1 = 1 PHASE—120/240 VOLTS; SUFFIX #3-2 = 3 PHASE 120/208 VOLTS; SUFFIX #3-3 = 3 PHASE—120/240 VOLTS; SUFFIX #3-4 = 3 PHASE—277/480 VOLTS, SUFFIX #3-16 = 3 PHASE-600 VOLT.

**SP, SPJD, SPVD, AND SPMD STANDBY GEN-SET STANDARD ACCESSORIES INCLUDE:** 12/24VDC "FLOAT" BATTERY CHARGER, SILENCER, FLEXIBLE OIL AND RADIATOR DRAIN HOSE, PROGRAMMABLE DIGITAL CONTROLLER, BATTERY TRAY AND CABLES, AND CIRCUIT BREAKER (SILENCER NOT INCLUDED FOR OPEN UNITS).